

# Package: sparkbq (via r-universe)

September 4, 2024

**Type** Package

**Title** Google 'BigQuery' Support for 'sparklyr'

**Version** 0.1.1

**URL** <http://www.mirai-solutions.com>,  
<https://github.com/miraisolutions/sparkbq>

**BugReports** <https://github.com/miraisolutions/sparkbq/issues>

**Description** A 'sparklyr' extension package providing an integration with Google 'BigQuery'. It supports direct import/export where records are directly streamed from/to 'BigQuery'. In addition, data may be imported/exported via intermediate data extracts on Google 'Cloud Storage'.

**Depends** R (>= 3.3.2)

**Imports** sparklyr (>= 0.7.0)

**Suggests** dplyr

**License** GPL-3 | file LICENSE

**SystemRequirements** Spark (>= 2.2.x)

**Encoding** UTF-8

**LazyData** yes

**RoxygenNote** 6.1.1

**Repository** <https://miraisolutions.r-universe.dev>

**RemoteUrl** <https://github.com/miraisolutions/sparkbq>

**RemoteRef** HEAD

**RemoteSha** b3e465589c2fb6d82f115c0f5cf487717f10e7f0

## Contents

bigquery_defaults . . . . .	2
default_bigquery_type . . . . .	3
default_billing_project_id . . . . .	4

default_dataset_location . . . . .	4
default_gcs_bucket . . . . .	5
default_service_account_key_file . . . . .	5
spark_read_bigquery . . . . .	6
spark_write_bigquery . . . . .	8

<b>Index</b>	<b>11</b>
--------------	-----------

---

bigquery_defaults	<i>Google BigQuery Default Settings</i>
-------------------	---

---

## Description

Sets default values for several Google BigQuery related settings.

## Usage

```
bigquery_defaults(billingProjectId, gcsBucket, datasetLocation = "US",
  serviceAccountKeyFile = NULL, type = "direct")
```

## Arguments

billingProjectId	Default Google Cloud Platform project ID for billing purposes. This is the project on whose behalf to perform BigQuery operations.
gcsBucket	Google Cloud Storage (GCS) bucket to use for storing temporary files. Temporary files are used when importing through BigQuery load jobs and exporting through BigQuery extraction jobs (i.e. when using data extracts such as Parquet, Avro, ORC, ...). The service account specified in serviceAccountKeyFile needs to be given appropriate rights. This should be the name of an existing storage bucket.
datasetLocation	Geographic location where newly created datasets should reside. "EU" or "US". Defaults to "US".
serviceAccountKeyFile	Google Cloud service account key file to use for authentication with Google Cloud services. The use of service accounts is highly recommended. Specifically, the service account will be used to interact with BigQuery and Google Cloud Storage (GCS). If not specified, Google application default credentials (ADC) will be used, which is the default.
type	Default BigQuery import/export type to use. Options include "direct", "parquet", "avro", "orc", "json" and "csv". Defaults to "direct". Please note that only "direct" and "avro" are supported for both importing and exporting. "csv" and "json" are not recommended due to their lack of type safety. See the table below for supported type and import/export combinations.

Direct	Parquet	Avro	ORC	JSON	CSV
--------	---------	------	-----	------	-----

Import to Spark (export from BigQuery)	X		X		X	X
Export from Spark (import to BigQuery)	X	X	X	X		

**Value**

A list of set options with previous values.

**References**

<https://github.com/miraisolutions/spark-bigquery> <https://cloud.google.com/bigquery/pricing> <https://cloud.google.com/bigquery/docs/dataset-locations> <https://cloud.google.com/bigquery/docs/authentication/service-account-file> <https://cloud.google.com/docs/authentication/> <https://cloud.google.com/bigquery/docs/authentication/> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-parquet> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-avro> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-orc> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-json> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage->

**See Also**

[spark\\_read\\_bigquery](#), [spark\\_write\\_bigquery](#), [default\\_billing\\_project\\_id](#), [default\\_gcs\\_bucket](#), [default\\_dataset\\_location](#)

---

default\_bigquery\_type *Default BigQuery import/export type*

---

**Description**

Returns the default BigQuery import/export type. It defaults to "direct".

**Usage**

```
default_bigquery_type()
```

**See Also**

[bigquery\\_defaults](#)

---

`default_billing_project_id`*Default Google BigQuery Billing Project ID*

---

**Description**

Returns the default Google BigQuery billing project ID.

**Usage**

```
default_billing_project_id()
```

**See Also**

[bigquery\\_defaults](#)

---

`default_dataset_location`*Default Google BigQuery Dataset Location*

---

**Description**

Returns the default Google BigQuery dataset location. It defaults to "US".

**Usage**

```
default_dataset_location()
```

**References**

<https://cloud.google.com/bigquery/docs/dataset-locations>

**See Also**

[bigquery\\_defaults](#)

---

default\_gcs\_bucket     *Default Google BigQuery GCS Bucket*

---

### **Description**

Returns the default Google BigQuery GCS bucket.

### **Usage**

```
default_gcs_bucket()
```

### **See Also**

[bigquery\\_defaults](#)

---

default\_service\_account\_key\_file  
*Default Google BigQuery Service Account Key File*

---

### **Description**

Returns the default service account key file to use.

### **Usage**

```
default_service_account_key_file()
```

### **References**

<https://cloud.google.com/bigquery/docs/authentication/service-account-file> <https://cloud.google.com/docs/authentication/> <https://cloud.google.com/bigquery/docs/authentication/>

### **See Also**

[bigquery\\_defaults](#)

---

 spark\_read\_bigquery    *Reading data from Google BigQuery*


---

### Description

This function reads data stored in a Google BigQuery table.

### Usage

```
spark_read_bigquery(sc, name,
  billingProjectId = default_billing_project_id(),
  projectId = billingProjectId, datasetId = NULL, tableId = NULL,
  sqlQuery = NULL, type = default_bigquery_type(),
  gcsBucket = default_gcs_bucket(),
  serviceAccountKeyFile = default_service_account_key_file(),
  additionalParameters = NULL, memory = FALSE, ...)
```

### Arguments

sc	<a href="#">spark_connection</a> provided by sparklyr.
name	The name to assign to the newly generated table (see also <a href="#">spark_read_source</a> ).
billingProjectId	Google Cloud Platform project ID for billing purposes. This is the project on whose behalf to perform BigQuery operations. Defaults to <code>default_billing_project_id()</code> .
projectId	Google Cloud Platform project ID of BigQuery dataset. Defaults to <code>billingProjectId</code> .
datasetId	Google BigQuery dataset ID (may contain letters, numbers and underscores). Either both of <code>datasetId</code> and <code>tableId</code> or <code>sqlQuery</code> must be specified.
tableId	Google BigQuery table ID (may contain letters, numbers and underscores). Either both of <code>datasetId</code> and <code>tableId</code> or <code>sqlQuery</code> must be specified.
sqlQuery	Google BigQuery SQL query. Either both of <code>datasetId</code> and <code>tableId</code> or <code>sqlQuery</code> must be specified. The query must be specified in standard SQL (SQL-2011). Legacy SQL is not supported. Tables are specified as ' <code>&lt;project_id&gt;.&lt;dataset_id&gt;.&lt;table_id&gt;</code> '.
type	BigQuery import type to use. Options include "direct", "avro", "json" and "csv". Defaults to <code>default_bigquery_type()</code> . See <a href="#">bigquery_defaults</a> for more details about the supported types.
gcsBucket	Google Cloud Storage (GCS) bucket to use for storing temporary files. Temporary files are used when importing through BigQuery load jobs and exporting through BigQuery extraction jobs (i.e. when using data extracts such as Parquet, Avro, ORC, ...). The service account specified in <code>serviceAccountKeyFile</code> needs to be given appropriate rights. This should be the name of an existing storage bucket.
serviceAccountKeyFile	Google Cloud service account key file to use for authentication with Google Cloud services. The use of service accounts is highly recommended. Specifically, the service account will be used to interact with BigQuery and Google Cloud Storage (GCS).

additionalParameters	Additional spark-bigquery options. See <a href="https://github.com/miraisolutions/spark-bigquery">https://github.com/miraisolutions/spark-bigquery</a> for more information.
memory	logical specifying whether data should be loaded eagerly into memory, i.e. whether the table should be cached. Note that eagerly caching prevents predicate pushdown (e.g. in conjunction with <a href="#">filter</a> ) and therefore the default is FALSE. See also <a href="#">spark_read_source</a> .
...	Additional arguments passed to <a href="#">spark_read_source</a> .

**Value**

A tbl\_spark which provides a dplyr-compatible reference to a Spark DataFrame.

**References**

<https://github.com/miraisolutions/spark-bigquery> <https://cloud.google.com/bigquery/docs/datasets> <https://cloud.google.com/bigquery/docs/tables> <https://cloud.google.com/bigquery/docs/reference/standard-sql/> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-avro> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-csv> <https://cloud.google.com/bigquery/pricing> <https://cloud.google.com/bigquery/docs/dataset-locations> <https://cloud.google.com/docs/authentication/> <https://cloud.google.com/bigquery/docs/authentication/>

**See Also**

[spark\\_read\\_source](#), [spark\\_write\\_bigquery](#), [bigquery\\_defaults](#)

Other Spark serialization routines: [spark\\_write\\_bigquery](#)

**Examples**

```
## Not run:
config <- spark_config()

sc <- spark_connect(master = "local", config = config)

bigquery_defaults(
  billingProjectId = "<your_billing_project_id>",
  gcsBucket = "<your_gcs_bucket>",
  datasetLocation = "US",
  serviceAccountKeyFile = "<your_service_account_key_file>",
  type = "direct")

# Reading the public shakespeare data table
# https://cloud.google.com/bigquery/public-data/
# https://cloud.google.com/bigquery/sample-tables
shakespeare <-
  spark_read_bigquery(
    sc,
    name = "shakespeare",
```

```

    projectId = "bigquery-public-data",
    datasetId = "samples",
    tableId = "shakespeare")

## End(Not run)

```

---

spark\_write\_bigquery    *Writing data to Google BigQuery*

---

## Description

This function writes data to a Google BigQuery table.

## Usage

```

spark_write_bigquery(data,
  billingProjectId = default_billing_project_id(),
  projectId = billingProjectId, datasetId, tableId,
  type = default_bigquery_type(), gcsBucket = default_gcs_bucket(),
  datasetLocation = default_dataset_location(),
  serviceAccountKeyFile = default_service_account_key_file(),
  additionalParameters = NULL, mode = "error", ...)

```

## Arguments

data	Spark DataFrame to write to Google BigQuery.
billingProjectId	Google Cloud Platform project ID for billing purposes. This is the project on whose behalf to perform BigQuery operations. Defaults to <code>default_billing_project_id()</code> .
projectId	Google Cloud Platform project ID of BigQuery dataset. Defaults to <code>billingProjectId</code> .
datasetId	Google BigQuery dataset ID (may contain letters, numbers and underscores).
tableId	Google BigQuery table ID (may contain letters, numbers and underscores).
type	BigQuery export type to use. Options include "direct", "parquet", "avro", "orc". Defaults to <code>default_bigquery_type()</code> . See <a href="#">bigquery_defaults</a> for more details about the supported types.
gcsBucket	Google Cloud Storage (GCS) bucket to use for storing temporary files. Temporary files are used when importing through BigQuery load jobs and exporting through BigQuery extraction jobs (i.e. when using data extracts such as Parquet, Avro, ORC, ...). The service account specified in <code>serviceAccountKeyFile</code> needs to be given appropriate rights. This should be the name of an existing storage bucket.
datasetLocation	Geographic location where newly created datasets should reside. "EU" or "US". Defaults to "US". Only needs to be specified if the dataset does not yet exist. It is ignored if it is specified and the dataset already exists.



serviceAccountKeyFile	Google Cloud service account key file to use for authentication with Google Cloud services. The use of service accounts is highly recommended. Specifically, the service account will be used to interact with BigQuery and Google Cloud Storage (GCS).
additionalParameters	Additional spark-bigquery options. See <a href="https://github.com/miraisolutions/spark-bigquery">https://github.com/miraisolutions/spark-bigquery</a> for more information.
mode	Specifies the behavior when data or table already exist. One of "overwrite", "append", "ignore" or "error" (default).
...	Additional arguments passed to <a href="#">spark_write_source</a> .

**Value**

NULL. This is a side-effecting function.

**References**

<https://github.com/miraisolutions/spark-bigquery> <https://cloud.google.com/bigquery/docs/datasets> <https://cloud.google.com/bigquery/docs/tables> <https://cloud.google.com/bigquery/docs/reference/standard-sql/> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-parquet> <https://cloud.google.com/bigquery/docs/loading-data-cloud-storage-orc> <https://cloud.google.com/bigquery/pricing> <https://cloud.google.com/bigquery/docs/dataset-locations> <https://cloud.google.com/docs/authentication/> <https://cloud.google.com/bigquery/docs/authentication/>

**See Also**

[spark\\_write\\_source](#), [spark\\_read\\_bigquery](#), [bigquery\\_defaults](#)

Other Spark serialization routines: [spark\\_read\\_bigquery](#)

**Examples**

```
## Not run:
config <- spark_config()

sc <- spark_connect(master = "local", config = config)

bigquery_defaults(
  billingProjectId = "<your_billing_project_id>",
  gcsBucket = "<your_gcs_bucket>",
  datasetLocation = "US",
  serviceAccountKeyFile = "<your_service_account_key_file>",
  type = "direct")

# Copy mtcars to Spark
spark_mtcars <- dplyr::copy_to(sc, mtcars, "spark_mtcars", overwrite = TRUE)

spark_write_bigquery(
```

```
data = spark_mtcars,  
datasetId = "<your_dataset_id>",  
tableId = "mtcars",  
mode = "overwrite")  
  
## End(Not run)
```

# Index

- \* **Spark serialization routines**

- spark\_read\_bigquery, 6

- spark\_write\_bigquery, 8

- \* **connection**

- bigquery\_defaults, 2

- spark\_read\_bigquery, 6

- spark\_write\_bigquery, 8

- \* **database**

- bigquery\_defaults, 2

- spark\_read\_bigquery, 6

- spark\_write\_bigquery, 8

bigquery\_defaults, 2, 3–9

default\_bigquery\_type, 3

default\_billing\_project\_id, 3, 4

default\_dataset\_location, 3, 4

default\_gcs\_bucket, 3, 5

default\_service\_account\_key\_file, 5

filter, 7

spark\_connection, 6

spark\_read\_bigquery, 3, 6, 9

spark\_read\_source, 6, 7

spark\_write\_bigquery, 3, 7, 8

spark\_write\_source, 9